

KWU

Kollmorgen Winding Unit

Kollmorgen's KWU Audible / Visual Emergency Handwinding Unit can be used to provide important feedback to service personnel about the position of the lift car under passenger entrapment conditions. Without such a unit it can be extremely difficult for a single Engineer to establish the exact position of the car, also whether or not the true car position permits

entrapped passengers to exit safely. KWU features a clear, easy-to-read display and On/Off hand-winding switch. This unit receives information about the car's exact position through a LON serial connection from the electromagnetic switch block unit mounted on the car. As the car is being hand-wound to the next stop, direction arrows and "above / below floor x"

information are given as well as confirmation of the actual floorlevel. The system is delivered complete, i.e. with electromagnetic switch block, magnets, pluggable buscable and floor display unit, ready for installation. KWU— an easily understood device providing vital information to assist the rescuing of entrapped passengers.

The electromagnetic switch block unit is mounted on the car in close proximity to one of the guide rails. Due to the special retainerof the switch block the magnets for triggering the signals can be easily placed on the guide rail.






Technichal Data

Terminals on the subassembly for connecting the magnetic switch

| | Terminal | Bus interfaces | Terminal | Power supply |
|--|----------|-------------------------------|----------|------------------------------------|
| | WH | Connecting network bus - high | WH | Earth |
| | WL | Connecting network bus - low | WL | Supply voltage 12 - 24 V DC; 70 mA |
| | | | | |
| | Terminal | Input terminals | Terminal | Input terminals |
| | | | | |
| | C1 | Magnetic switch 12a | C3 | Magnet switch 13a |

Connecting Subassemblies



The terminals WH and WL connect between both subassemblies.

The power supply can be made through the 12 V emergency lighting units in the control system.

| Article Number | Description |
|----------------|--|
| 8S40-40-180 | Remote Hand Winding Unit Set with Magnetswitch and Cable |
| 2N11-03-024 | Magnet Holder MH24 - 1 Correction/Prelimit Switch Bottom |
| 2N11-03-023 | Magnet Holder MH23 - 1 Correction/Prelimit Switch Top |
| 2N10-70-001 | Switch Magnet SC 15 Red Color South Pole |